



GENERAL NOTES

- 1) DO NOT SCALE DIMENSIONS.
- 2) REFER TO CIVIL DRAWINGS FOR GRADING, UTILITY AND ADJACENT LAND/USE INFORMATION.
- 3) REFER TO ARCHITECTURAL FOR BUILDING AND LANDSCAPE INFORMATION.
- 4) VERIFY LOCATION OF ALL EXISTING AND UNDERSHOWN UTILITIES BEFORE BEGINNING WORK.
- 5) VERIFY THE EXISTING LOCATION OF ANY OBSTRUCTIONS FOUND IN PLACE OR EXISTING FROM RECORD SHALL RESULT IN CONSTRUCTION CHANGE. RESPONSIBILITY FOR ANY AND ALL EXISTING UTILITIES SHALL REMAIN WITH THE CONTRACTOR.
- 6) CONSTRUCTION OF SITE OBSTRUCTIONS ARE ONLY MADE BY EXISTING WALL, FOUNDATION OR FOOTING FOUND AS SHOWN ON PLAN. STATE AGENCIES MUST BE NOTIFIED AND OBTAIN PERMITS PRIOR TO REMOVAL WORK.
- 7) WHERE OBSTRUCTIONS ARE IN FEET ONLY, CONTRACTOR IS TO ASSUME THEIR AGE OF (E.G. "12" = "12'-0")
- 8) LAYOUT OF STAKE LOCATIONS OF EXISTING SITE WALLS, FOUNDATIONS, FOUNDATIONS, UTILITY LOCATIONS, SHALL BE VERIFIED BY THE CONTRACTOR PRIOR TO CONSTRUCTION.

RUBBERIZED TRACK NOTES

- 1) REFER TO SPECIFICATION OF THE RUBBERIZED SURFACE THE FINISH SHALL BE CHECKED AND APPROVED BY THE ARCHITECT PRIOR TO CONSTRUCTION.
- 2) FROM VARIATE PLANNING OF CONCRETE SHALL NOT SPREAD MORE THAN 1/2" WHEN MIXED WITH A 1" TO 1 1/2" STRENGTH FILL IN ALL DIRECTIONS.
- 3) THE CONTRACTOR SHALL PROTECT ALL QUALITY AREAS FROM ANY OBSTRUCTION FROM THE RUBBERIZED SURFACE PRIOR TO CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING ALL QUALITY AREAS FROM ANY OBSTRUCTION FROM THE RUBBERIZED SURFACE PRIOR TO CONSTRUCTION.
- 4) IMMEDIATELY PRIOR TO APPLICATION OF RUBBERIZED SURFACE, THE CONCRETE SHALL BE THOROUGHLY CLEANED AND ALL SURFACES TO BE RUBBERIZED SHALL BE THOROUGHLY CLEANED AND ALL SURFACES TO BE RUBBERIZED SHALL BE THOROUGHLY CLEANED.
- 5) THE RUBBERIZED SURFACE SHALL BE THOROUGHLY CLEANED AND ALL SURFACES TO BE RUBBERIZED SHALL BE THOROUGHLY CLEANED.
- 6) THE RUBBERIZED SURFACE SHALL BE THOROUGHLY CLEANED AND ALL SURFACES TO BE RUBBERIZED SHALL BE THOROUGHLY CLEANED.
- 7) MAKE ALL JOINTS OF RUBBERIZED SURFACE TO BE SPACED WITH STRENGTHENING STRIPS.
- 8) INSTALL TRACERY BARRIERS INCLUDING RUBBERIZED SURFACE.

SCALE: 1/4"=1'-0"



L1.0
OVERALL SITE PLAN

NAC ARCHITECTURE

BELLEVUE SCHOOL DISTRICT
TILLICUM MIDDLE SCHOOL
16000 SE 15TH ST. BELLEVUE, WA 98008

WEISMANDESIGNGROUP
LANDSCAPE ARCHITECTURE

65% STAGE -
CONDITIONAL USE SUBMITTAL

REVISIONS



TILLICUM MIDDLE SCHOOL

SITE AMENITIES



NAC

ARCHITECTURE



CANOPY PERSPECTIVE



Received

MAR 26 2015

Permit Processing